

29 mm (1.13") photomultiplier

9407B series data sheet

1 description

The 9407B is a 29 mm (1.13") diameter, end window photomultiplier with magnesium fluoride window, enhanced green sensitive bialkali photocathode and 11 high gain, high stability, SbCs dynodes of linear focused design.

It is supplied with spectral response data at specific wavelengths in the vacuum ultra-violet and with photon counting plateau curves showing the recommended voltage for photon counting applications.

2 applications

- fluorescence studies from 110 nm to 680 nm

3 features

- sensitive to vacuum ultra-violet light


4 window characteristics

The plane of the window is cut perpendicular to its optical axis.

9407B magnesium fluoride	
spectral range (nm)*	110 - 680
refractive index (n_d)	1.38

* wavelength range over which quantum efficiency exceeds 1 % of peak

5 typical spectral response curves




6 characteristics

	unit	min	typ	max
photocathode: bialkali				
active diameter	mm		25	
quantum efficiency at peak	%		25	
luminous sensitivity	$\mu\text{A/lm}$		75	
with CB filter		7	10	
with CR filter			5	
dynodes: 11LFSbCs				
anode sensitivity in divider A:				
nominal anode sensitivity	A/lm		200	
max. rated anode sensitivity	A/lm		2000	
overall V for nominal A/lm	V		1050	1300
overall V for max. rated A/lm	V		1400	
gain at nominal A/lm	$\times 10^6$		3	
dark current at 20 °C:				
dc at nominal A/lm	nA		0.3	5
dc at max. rated A/lm	nA		3	
dark count rate	s^{-1}		200	
pulsed linearity (-5% deviation):				
divider A	mA		25	
divider B	mA		100	
rate effect (I_a for $\Delta g/g=1\%$):	μA		20	
magnetic field sensitivity:				
the field for which the output decreases by 50 %				
most sensitive direction	$\text{T} \times 10^{-4}$		1.6	
temperature coefficient:	$\% \text{ } ^\circ\text{C}^{-1}$		± 0.5	
timing:				
single electron rise time	ns		4.5	
single electron (fwhm)	ns		7.5	
single electron jitter (fwhm)	ns		4	
transit time	ns		33	
weight:	g		50	
maximum ratings:				
anode current	μA			100
cathode current	nA			50
gain	$\times 10^6$			27
sensitivity	A/lm			2000
temperature	$^\circ\text{C}$	-30		60
V (k-a) ⁽¹⁾	V			2000
V (k-d1)	V			300
V (d-d) ⁽²⁾	V			300
ambient pressure (absolute)	kPa			202

⁽¹⁾ subject to not exceeding max. rated sensitivity ⁽²⁾ subject to not exceeding max rated V(k-a)

7 typical voltage gain characteristics




8 voltage divider distribution


	k	d ₁	d ₂	d ₈	d ₉	d ₁₀	d ₁₁	a	
A	2R	R	R	R	R	R	R	R	Standard
B	2R	R	R	2R	3R	4R	3R		High Pulsed Linearity

Characteristics contained in this data sheet refer to divider A unless stated otherwise.

9 external dimensions mm



10 base configuration (viewed from below)



Our range of B14B sockets, available for this series, includes versions with or without a mounting flange, and versions with contacts for mounting directly onto printed circuit boards.

11 high voltage caution

To avoid arc discharges between the photocathode and nearby grounded surfaces apply the HV only after hard vacuum has been attained, that is when the pressure is less than 10⁻³ torr. Failure to observe this precaution will destroy the pmt and invalidate the warranty.

12 handling instructions

The window of this pmt has been specially cleaned to give maximum efficiency. It should not be touched with fingers or allowed to come into contact with oil or grease. The window can be cleaned with isopropyl alcohol to remove oil deposits.

13 ordering information

The 9407B meets the specification given in this data sheet. You may order **variants** by adding a suffix to the type number. You may also order **options** by adding a suffix to the type number. You may order product with **specification options** by discussing your requirements with us. If your selection option is for one-off order, then the product will be referred to as 9407A. For a repeat order, ET Enterprises will give the product a two digit suffix after the letter B, for example B21. This identifies your specific requirement.


9407

options

- E** electrostatic shielding
see drawing below
- S** electromagnetic shielding
see drawing below

specification options

- B** as given in data sheet
- A** single order to selected specification
- Bnn** repeat order to selected specification



14 voltage dividers

The standard voltage dividers available for these pmts are tabulated below:

	k	d ₁	d ₂	d ₇	d ₈	d ₉	d ₁₀	d ₁₁	a
C637A	2R	R	R	R	R	R	R	R	
C637B	2R	R	R	2R	3R	4R	3R		
C637C	150 V	R	R	R	R	R	R		
C637D	150 V	R	R	2R	3R	4R	3R		

R = 330kΩ

*mumetal is a registered trademark of Magnetic Shield Corporation

ET Enterprises Limited
45 Riverside Way
Uxbridge UB8 2YF
United Kingdom
tel: +44 (0) 1895 200880
fax: +44 (0) 1895 270873
e-mail: sales@et-enterprises.com
web site: www.et-enterprises.com

ADIT Electron Tubes
300 Crane Street
Sweetwater TX 79556 USA
tel: (325) 235 1418
toll free: (800) 399 4557
fax: (325) 235 2872
e-mail: sales@electron tubes.com
web site: www.electrontubes.com

choose accessories for this pmt on our website

an ISO 9001 registered company

The company reserves the right to modify these designs and specifications without notice. Developmental devices are intended for evaluation and no obligation is assumed for future manufacture. While every effort is made to ensure accuracy of published information the company cannot be held responsible for errors or consequences arising therefrom.



© ET Enterprises Ltd, 2012
DS_9407B Issue 10 (23/01/12)