


## 403/95 nm BrightLine® Full Spectrum Blocking single-band bandpass filter

Part Number: FF01-403/95-25



**Semrock**  
A Unit of **IPXC** Corporation

### Semrock, Inc

3625 Buffalo Road, Suite 6  
Rochester, New York 14624

Main Phone: +1 585.594.7050 (worldwide)  
Toll Free Phone: 866.736.7625 (866-SEMROCK)  
(within US and Canada)

Your filter spectrum may differ slightly from the typical spectrum above, but is certified to meet the optical specifications noted below.



### 403/95 nm BrightLine® Full Spectrum Blocking single-band bandpass filter

BrightLine® Full Spectrum Blocking single-band bandpass filter has been optimized to provide extended blocking down to UV wavelengths (250nm) and up to the near infrared (NIR) and paired with a combination of VersaChrome Edge™ tunable long-wave-pass (TLP) and tunable short-wave-pass (TSP) filters to custom bandpass filters as narrow as sub 5 nm FWHM or as wide as 12% of the center wavelength throughout the visible and near-infrared wavelength range.

FF01-403/95 is compatible with [TLP01-448](#) and [TSP01-448](#) VersaChrome Edge™ tunable filters.

Visit our [VersaChrome Edge™ tunable filters page](#) for additional information.

Part Number	Size	Price <sup>1</sup>	Stock Status
FF01-403/95-25	25 mm x 3.5 mm	\$355	In Stock

Don't see a size you need? Contact us for custom sizing – available in less than a week (sizing fee applies).

1) US domestic pricing only. If you are ordering from outside the US, please contact your nearest [regional distributor](#) for the correct list price.

### Optical Specifications

Specification	Value
Transmission Band 1	T <sub>avg</sub> > 90% 355 – 450 nm
Center Wavelength 1	403 nm
Guaranteed Minimum Bandwidth 1	95 nm
FWHM Bandwidth 1 (nominal)	99.2 nm
Blocking Band 1	OD <sub>avg</sub> > 6 250 – 348 nm
Blocking Band 2	OD <sub>avg</sub> > 6 459 – 1200 nm
Blocking Band 3	

### General Filter Specifications

Specification	Value
Angle of Incidence	0 ± 5 degrees
Cone Half-angle	7 degrees
Optical Damage Rating	Testing has proven to show no signs of degradation when exposed to at least 6.0 W of power from an unfiltered xenon arc lamp over a 25 mm diameter (corresponding to 1.2 W/cm <sup>2</sup> ) for over 500 hrs.
Effective Index	2.05

### Physical Filter Specifications (applies to standard sized parts; contact us regarding other sizes)

Specification	Value
Transverse Dimensions (Diameter)	25 mm
Transverse Tolerance (mounted)	+ 0.0 / - 0.1 mm
Filter Thickness (Mounted)	3.5 mm
Filter Thickness Tolerance (Mounted)	± 0.1 mm
Clear Aperture	≥ 22 mm
Scratch-Dig	60-40

Substrate Thickness (unmounted)	2.0 mm
Substrate Thickness Tolerance (unmounted)	± 0.1 mm
Orientation	Arrow on ring indicates preferred direction of propagation of light