


488/568 nm Yokogawa emission filter

Part Number: Em01-R488/568-25



Semrock, Inc

3625 Buffalo Road, Suite 6
Rochester, New York 14624

Main Phone: +1 585.594.7050 (worldwide)
Toll Free Phone: 866.736.7625 (866-SEMROCK)
(within US and Canada)

Your filter spectrum may differ slightly from the typical spectrum above, but is certified to meet the optical specifications noted below.



488/568 nm Yokogawa emission filter

Combining superior performance with exceptional durability, these filters are specifically optimized for use with all Yokogawa CSU spinning-disk scan head system configurations.

Part Number	Size	Price ¹	Stock Status
Em01-R488/568-25	25 mm x 3.5 mm	\$405	In Stock

Don't see a size you need? Contact us for custom sizing – available in less than a week (sizing fee applies).

1) US domestic pricing only. If you are ordering from outside the US, please contact your nearest [regional distributor](#) for the correct list price.

Optical Specifications

Specification	Value
Transmission Band 1	T _{avg} > 90% 503 – 546 nm
Center Wavelength 1	524.5 nm
Guaranteed Minimum Bandwidth 1	43 nm
FWHM Bandwidth 1 (nominal)	52.5 nm
Transmission Band 2	T _{avg} > 90% 583 – 700 nm
Center Wavelength 2	641.5 nm
Guaranteed Minimum Bandwidth 2	117 nm
FWHM Bandwidth 2 (nominal)	132.4 nm
Blocking Band 1	OD _{dabs} > 6 405 nm
Blocking Band 2	OD _{dabs} > 6 442 nm
Blocking Band 3	OD _{dabs} > 6 488 nm
Blocking Band 4	OD _{dabs} > 6 561 – 568 nm

General Filter Specifications

Specification	Value
Angle of Incidence	0 ± 5 degrees
Cone Half-angle	7 degrees
Optical Damage Rating	Testing has proven to show no signs of degradation when exposed to at least 6.0 W of power from an unfiltered xenon arc lamp over a 25 mm diameter (corresponding to 1.2 W/cm ²) for over 500 hrs.
Effective Index	1.76

Physical Filter Specifications (applies to standard sized parts; contact us regarding other sizes)

Specification	Value
Transverse Dimensions (Diameter)	25 mm
Transverse Tolerance (mounted)	+ 0.0 / - 0.1 mm

Filter Thickness (Mounted)	3.5 mm
Filter Thickness Tolerance (Mounted)	± 0.1 mm
Clear Aperture	≥ 80%
Scratch-Dig	60-40
Substrate Thickness (unmounted)	2.0 mm
Substrate Thickness Tolerance (unmounted)	± 0.1 mm
Orientation	Arrow on ring indicates preferred direction of propagation of light