


465/537/623 nm BrightLine® triple-band bandpass filter

Part Number: FF01-465/537/623-25



Semrock, Inc

3625 Buffalo Road, Suite 6
Rochester, New York 14624

Main Phone: +1 585.594.7050 (worldwide)
Toll Free Phone: 866.736.7625 (866-SEMROCK)
(within US and Canada)

Your filter spectrum may differ slightly from the typical spectrum above, but is certified to meet the optical specifications noted below.



465/537/623 nm BrightLine® triple-band bandpass filter

Individual multiband fluorescence bandpass filters that utilize Semrock's patented single-substrate construction. These filters have extremely high transmission, steep and well-defined edges, and outstanding blocking between the passbands. All thin-film, hard-coated construction for unsurpassed performance and reliability.

Part Number	Size	Price ¹	Stock Status
FF01-465/537/623-25	25 mm x 3.5 mm	\$435	In Stock
FF01-465/537/623-23.3-D	23.3 mm x 2.0 mm (unmounted)	\$435	2nd Day Ship

Don't see a size you need? Contact us for custom sizing – available in less than a week (sizing fee applies).

1) US domestic pricing only. If you are ordering from outside the US, please contact your nearest [regional distributor](#) for the correct list price.

Optical Specifications

Specification	Value
Transmission Band 1	T _{avg} > 90% 450 – 480 nm
Center Wavelength 1	465 nm
Guaranteed Minimum Bandwidth 1	30 nm
FWHM Bandwidth 1 (nominal)	36.5 nm
Transmission Band 2	T _{avg} > 90% 527 – 547 nm
Center Wavelength 2	537 nm
Guaranteed Minimum Bandwidth 2	20 nm
FWHM Bandwidth 2 (nominal)	27 nm
Transmission Band 3	T _{avg} > 90% 598 – 648 nm
Center Wavelength 3	623 nm
Guaranteed Minimum Bandwidth 3	50 nm
FWHM Bandwidth 3 (nominal)	59.8 nm
Blocking Band 1	OD _{avg} > 4 275 – 327 nm
Blocking Band 2	OD _{avg} > 8 327 – 437 nm (Design specification - measurements are noise-floor limited)
Blocking Band 3	OD _{avg} > 8 494 – 512 nm (Design specification - measurements are noise-floor limited)
Blocking Band 4	OD _{avg} > 8 563 – 581 nm (Design specification - measurements are noise-floor limited)
Blocking Band 5	OD _{avg} > 4 664 – 925 nm

General Filter Specifications

Specification	Value
Angle of Incidence	0 ± 5 degrees
Cone Half-angle	7 degrees

Optical Damage Rating: Testing has proven to show no signs of degradation when exposed to at least 6.0 W of power from an unfiltered

Optical Damage Rating xenon arc lamp over a 25 mm diameter (corresponding to 1.2 W/cm²) for over 500 hrs.

Effective Index 1.97

Physical Filter Specifications (applies to standard sized parts; contact us regarding other sizes)

Specification	Value
Transverse Dimensions (Diameter)	25 mm
Transverse Tolerance (mounted)	+ 0.0 / - 0.1 mm
Filter Thickness (Mounted)	3.5 mm
Filter Thickness Tolerance (Mounted)	± 0.1 mm
Clear Aperture	≥ 22 mm
Scratch-Dig	60-40
Substrate Thickness (unmounted)	2.0 mm
Substrate Thickness Tolerance (unmounted)	± 0.1 mm
Orientation	Arrow on ring indicates preferred direction of propagation of light