


## 266 nm Laser BrightLine® single-edge laser-flat dichroic beamsplitter

Part Number: Di01-R266-25x36



**Semrock**  
A Unit of IPXX Corporation

### Semrock, Inc

3625 Buffalo Road, Suite 6  
Rochester, New York 14624

Main Phone: +1 585.594.7050 (worldwide)  
Toll Free Phone: 866.736.7625 (866-SEMROCK)  
(within US and Canada)

Your filter spectrum may differ slightly from the typical spectrum above, but is certified to meet the optical specifications noted below.



### 266 nm Laser BrightLine® single-edge laser-flat dichroic beamsplitter

The perfect beamsplitters for the most popular lasers used in fluorescence imaging, including newer all-solid-state lasers. All beamsplitters in this category have exceptional reflectance at the laser wavelengths, improved ("laser-grade") flatness, and anti-reflection (AR) coatings to minimize imaging artifacts resulting from the coherent laser light.

Part Number	Size	Price <sup>1</sup>	Stock Status
Di01-R266-25x36	25.2 mm x 35.6 mm x 1.1 mm (unmounted)	\$495	In Stock

Don't see a size you need? Contact us for custom sizing – available in less than a week (sizing fee applies).

<sup>1</sup> US domestic pricing only. If you are ordering from outside the US, please contact your nearest [regional distributor](#) for the correct list price.

### Optical Specifications

Specification	Value
Reflection Band 1	Rabs > 94% 245 – 266 nm
Reflection Band 1 (p-pol)	Rabs > 90% 245 – 266 nm
Reflection Band 1 (s-pol)	Rabs > 98% 245 – 266 nm
Reflection Band 2	Ravg > 90% 230 – 245 nm
Edge Wavelength 1	273 nm
Transmission Band 1	Tavg > 90% 277 – 1200 nm
Laser Wavelengths 1	266 nm

### General Filter Specifications

Specification	Value
Angle of Incidence	45 degrees with a shift of < 0.2%/degree (40 – 50 degrees)
Cone Half-angle	0.5 degrees
Optical Damage Rating	Not Tested
Flatness	<a href="#">Laser Flat</a>
Steepness	Steep
Effective Index	2.17

### Physical Filter Specifications (applies to standard sized parts; contact us regarding other sizes)

Specification	Value
Transverse Dimensions (L x W)	25.2 mm x 35.6 mm
Transverse Tolerance	± 0.1 mm
Filter Thickness (unmounted)	1.05 mm
Filter Thickness Tolerance (unmounted)	± 0.05 mm
Clear Aperture	≥ 80% (elliptical)

Scratch-Dig	60-40
Substrate Type	Fused Silica
Substrate Thickness (unmounted)	1.05 mm
Substrate Thickness Tolerance (unmounted)	± 0.05 mm
Orientation	Reflective surface marked with part number - Orient in direction of incoming light