


776 nm blocking edge BrightLine® long-pass filter

Part Number: FF01-776/LP-25



Semrock
A Unit of **IPX** Corporation

Semrock, Inc

3625 Buffalo Road, Suite 6
Rochester, New York 14624

Main Phone: +1 585.594.7050 (worldwide)
Toll Free Phone: 866.736.7625 (866-SEMROCK)
(within US and Canada)

Your filter spectrum may differ slightly from the typical spectrum above, but is certified to meet the optical specifications noted below.



776 nm blocking edge BrightLine® long-pass filter

Individual fluorescence long-pass and short-pass filters that have been optimized for use in a variety of fluorescence instruments. All thin-film, hard-coated construction for unsurpassed performance and reliability.

Part Number	Size	Price ¹	Stock Status
FF01-776/LP-25	25 mm x 3.5 mm	\$355	In Stock
FF01-776/LP-32	32 mm x 3.5 mm	\$582	2nd Day Ship
FF01-776/LP-23.3-D	23.3 mm x 2.0 mm (unmounted)	\$355	2nd Day Ship

Don't see a size you need? Contact us for custom sizing – available in less than a week (sizing fee applies).

¹ US domestic pricing only. If you are ordering from outside the US, please contact your nearest [regional distributor](#) for the correct list price.

Optical Specifications

Specification	Value
Transmission Band 1	T _{avg} > 93% 789 – 1200 nm
Edge Wavelength 1	785 nm
Blocking Band 1	OD _{avg} > 1 200 – 400 nm
Blocking Band 2	OD _{avg} > 2 400 – 545 nm
Blocking Band 3	OD _{avg} > 5 545 – 718.6 nm
Blocking Band 4	OD _{avg} > 10 731 – 764 nm (Design specification - measurements are noise-floor limited)
Blocking Band 5	OD > 3.5 776.5 nm

General Filter Specifications

Specification	Value
Angle of Incidence	0 ± 5 degrees
Cone Half-angle	7 degrees
Optical Damage Rating	Testing has proven to show no signs of degradation when exposed to at least 6.0 W of power from an unfiltered xenon arc lamp over a 25 mm diameter (corresponding to 1.2 W/cm ²) for over 500 hrs.
Effective Index	1.72

Physical Filter Specifications (Applies to standard sized parts. Contact us regarding other sizes.)

Specification	Value
Transverse Dimensions (Diameter)	25 mm
Transverse Tolerance (mounted)	+ 0.0 / - 0.1 mm
Filter Thickness (Mounted)	3.5 mm
Filter Thickness Tolerance (Mounted)	± 0.1 mm

Clear Aperture	≥ 22 mm
Scratch-Dig	60-40
Substrate Thickness (unmounted)	2.0 mm
Substrate Thickness Tolerance (unmounted)	± 0.1 mm
Orientation	Arrow on ring indicates preferred direction of propagation of light