


## 568 nm EdgeBasic™ best-value long-pass edge filter

Part Number: BLP01-568R-25



### Semrock, Inc

3625 Buffalo Road, Suite 6  
Rochester, New York 14624

Main Phone: +1 585.594.7050 (worldwide)  
Toll Free Phone: 866.736.7625 (866-SEMROCK)  
(within US and Canada)

Your filter spectrum may differ slightly from the typical spectrum above, but is certified to meet the optical specifications noted below.



### 568 nm EdgeBasic™ best-value long-pass edge filter

EdgeBasic filters offer an ideal combination of performance and value for applications including Raman spectroscopy and fluorescence imaging and measurements. They offer exceptional laser-line blocking and high transmission for Raman applications that do not require measuring the smallest possible Raman shifts and when cost is an issue.

Part Number	Size	Price <sup>1</sup>	Stock Status
BLP01-568R-25	25 mm x 3.5 mm	\$355	In Stock

Don't see a size you need? Contact us for custom sizing – available in less than a week (sizing fee applies).

1) US domestic pricing only. If you are ordering from outside the US, please contact your nearest [regional distributor](#) for the correct list price.

### Optical Specifications

Specification	Value
Transmission Band 1	T <sub>avg</sub> > 93% 584.1 – 900 nm
Edge Wavelength 1	579 nm
Blocking Band 1	OD <sub>avg</sub> > 5 200 – 448.8 nm
Blocking Band 2	OD <sub>abs</sub> > 6 448.8 – 568.2 nm
Transition Width (nm)	14.2 nm
Transition Width (cm <sup>-1</sup> )	429 cm <sup>-1</sup>

### General Filter Specifications

Specification	Value
Laser Wavelength 1	568.2 nm
Laser Wavelength 1 (low)	561 nm
Laser Wavelength 1 (high)	568.2 nm
Angle of Incidence	0 ± 2 degrees
Cone Half-angle	5 degrees
Optical Damage Rating	Not tested
Effective Index	1.82

### Physical Filter Specifications (applies to standard sized parts; contact us regarding other sizes)

Specification	Value
Transverse Dimensions (Diameter)	25 mm
Transverse Tolerance (mounted)	+ 0.0 / - 0.1 mm
Filter Thickness (Mounted)	3.5 mm
Filter Thickness Tolerance (Mounted)	± 0.1 mm
Clear Aperture	≥ 22 mm
Scratch/Dig	60/40

Scratch-Dig	00-40
Substrate Thickness (unmounted)	2.0 mm
Substrate Thickness Tolerance (unmounted)	$\pm 0.1$ mm
Orientation	Arrow on ring indicates preferred direction of propagation of light