


515 nm blocking edge BrightLine® long-pass filter

Part Number: FITC-LP01-Clin-25



Semrock, Inc

3625 Buffalo Road, Suite 6
Rochester, New York 14624

Main Phone: +1 585.594.7050 (worldwide)
Toll Free Phone: 866.736.7625 (866-SEMROCK)
(within US and Canada)

Your filter spectrum may differ slightly from the typical spectrum above, but is certified to meet the optical specifications noted below.



515 nm blocking edge BrightLine® long-pass filter

Individual fluorescence long-pass and short-pass filters that have been optimized for use in a variety of fluorescence instruments. All thin-film, hard-coated construction for unsurpassed performance and reliability.

Part Number	Size	Price ¹	Stock Status
FITC-LP01-Clin-25	25 mm x 3.5 mm	\$305	In Stock
FITC-LP01-Clin-23.3-D	23.3 mm x 2.0 mm (unmounted)	\$305	2nd Day Ship

This part is not available for custom sizing.

1) US domestic pricing only. If you are ordering from outside the US, please contact your nearest [regional distributor](#) for the correct list price.

Optical Specifications

Specification	Value
Transmission Band 1	T _{avg} > 90% 519 – 700 nm
Edge Wavelength 1	515 nm
Blocking Band 1	OD _{avg} > 5 200 – 449 nm
Blocking Band 2	OD _{avg} > 8 449 – 489.5 nm (Design specification - measurements are noise-floor limited)
Blocking Band 3	OD > 5 500.5 nm

General Filter Specifications

Specification	Value
Angle of Incidence	0 ± 5 degrees
Cone Half-angle	7 degrees
Optical Damage Rating	Testing has proven to show no signs of degradation when exposed to at least 6.0 W of power from an unfiltered xenon arc lamp over a 25 mm diameter (corresponding to 1.2 W/cm ²) for over 500 hrs.
Effective Index	1.89

Physical Filter Specifications (applies to standard sized parts; contact us regarding other sizes)

Specification	Value
Transverse Dimensions (Diameter)	25 mm
Transverse Tolerance (mounted)	+ 0.0 / - 0.1 mm
Filter Thickness (Mounted)	3.5 mm
Filter Thickness Tolerance (Mounted)	± 0.1 mm
Clear Aperture	≥ 22 mm
Scratch-Dig	60-40
Substrate Thickness (unmounted)	2.0 mm

Substrate Thickness Tolerance (unmounted)

± 0.1 mm

Orientation

Arrow on ring indicates preferred direction of propagation of light